

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions,  
and listings, of claims in the application:

**LISTING OF CLAIMS**

1.(Currently Amended) A scrubber for the cleaning of gases,  
comprising:

a scrubber tower;

a plurality of scrubber stages, each arranged in the  
scrubber tower with different ones of the plurality of scrubber  
stages at different levels above each other in the scrubber  
tower, at least one of the plurality of scrubber stages above a  
lowest one of said plurality of scrubber stages comprises a ring-  
shaped fluid storage tank arranged inside the scrubber tower and  
is arranged surrounding a central channel through which the gas  
that is to be cleaned can pass upwards; and

a separation trough at the bottom of each of the plurality  
of stages of the scrubber above the lowest one of the plurality  
of scrubber stages and arranged separating the fluid from the  
upwards flowing gas, the separation trough having obliquely  
placed laminae leading the fluid that arrives from one of the  
plurality of scrubber stages disposed above the separation trough  
to trough channels arranged under the laminae that lead the fluid  
onwards to the corresponding ring-shaped fluid storage tank,

~~wherein at least one of the plurality of scrubber stages~~  
~~above a lowest one of said plurality of scrubber stages comprises~~  
~~a ring-shaped fluid storage tank arranged inside the scrubber~~  
~~tower and is arranged surrounding a central channel through which~~  
~~the gas that is to be cleaned can pass upwards~~ the separation  
trough is recessed within and surrounded by the ring-shaped fluid  
storage tank.

2.(Previously Presented) The scrubber according to claim 1,  
wherein each of the plurality of scrubber stages above the lowest  
of the plurality of scrubber stages comprises the ring-shaped  
fluid storage tank located inside of the scrubber tower.

3.(Previously Presented) The scrubber according to claim 1,  
further comprising a circulation pump at each of the plurality of  
scrubber stages and arranged to feed fluid through feed pipes  
present in the corresponding ring-shaped fluid storage tank from  
the corresponding ring-shaped fluid storage tank at the bottom of  
the scrubber stage to spray beams arranged at the upper part of  
the scrubber stage for distribution over the cross-section of the  
scrubber in a direction against the up-wards gas flow.

4.(Canceled)

5.(Canceled)

6.(Previously Presented) The scrubber according to claim 3, wherein the circulation pump is arranged connected to the corresponding ring-shaped fluid storage tank and located at essentially the same level as the ring-shaped fluid storage tank.

7.(Previously Presented) The scrubber according to claim 6, wherein the circulation pump is arranged outside of the corresponding ring-shaped fluid storage tank and outside of the scrubber tower, and is connected by means of an inlet pipe to a connection on the corresponding ring-shaped fluid storage tank.

8.(Previously Presented) The scrubber according to claim 6, further comprising a pump tank arranged outside of the corresponding ring-shaped fluid storage tank and outside of the scrubber tower and directly connected to the corresponding ring-shaped fluid storage tank through a connection, and the circulation pump is arranged in or connected to the pump tank.

9.(Previously Presented) The scrubber according to claim 3, wherein the circulation pump is arranged on the ground outside of the corresponding ring-shaped fluid storage tank and outside of the scrubber tower, and connected by means of an inlet pipe to a connector on the corresponding ring-shaped fluid storage tank.

10.(Previously Presented) The scrubber according to claim 3, wherein the feed pipe feeding the fluid to the spray beams is located inside an outer surface of the scrubber tower.

11.(Previously Presented) The scrubber according to claim 2, further comprising a circulation pump at each of the plurality of scrubber stages and arranged to feed fluid through feed pipes present in the corresponding ring-shaped fluid storage tank from the corresponding ring-shaped fluid storage tank at the bottom of the scrubber stage to spray beams arranged at the upper part of the scrubber stage for distribution over the cross-section of the scrubber in a direction against the up-wards gas flow.

12.(Previously Presented) The scrubber according to claim 4, wherein the circulation pump is connected to the corresponding ring-shaped fluid storage tank and located at essentially the same level as the corresponding ring-shaped fluid storage tank.

13.(Previously Presented) The scrubber according to claim 5, wherein the circulation pump is connected to the corresponding ring-shaped fluid storage tank and located at essentially the same level as the corresponding ring-shaped fluid storage tank.

14.(Previously Presented) The scrubber according to claim 4, wherein the circulation pump is arranged on ground outside of the corresponding ring-shaped fluid storage tank and outside of the scrubber tower, and connected by means of an inlet pipe to a connector on the corresponding ring-shaped fluid storage tank.

15.(Previously Presented) The scrubber according to claim 5, wherein the circulation pump is arranged on a ground outside of the corresponding ring-shaped fluid storage tank and outside of the scrubber tower, and connected by means of an inlet pipe to a connector on the corresponding ring-shaped fluid storage tank.